

800-4310 Solvent G (100-134) (012-0300)

Product codes: 800-4310 Solvent G	Viscosity	N/A
	Flash Point:	63°C
	Density (kg/l):	0.90 ± 2% at 25°C
	Solid (% by weight):	0%
	Solid (% by volume):	0%
	Shelf Life (months):	Unlimited

Product Description:

Aromatic solvent with a very slow evaporation rate. It may be used as a very slow reducer for oil or alkyd based stains and coatings. Solvent G may be referred to as Solvesso 150 or heavy aromatic solvent naphtha.

Uses:

Slow solvent used to slow the drying of glazes and wiping stain such as 151-1310 and 825-9000.

Environmental Data (as supplied):	VOC less exempt g/l:	898
	VOC g/l:	898

Note:

See individual compliance sheets for specific data

Application Data	Suggested uses:	N/A
	Mixing Ratio:	See Technical bulletin of the product to be reduced
	Pot life:	N/A
	Application Viscosity:	N/A
	Reducer:	N/A
	Retarder:	N/A
	Clean-up Solvent:	N/A
	Recommended Wet Film:	N/A
	Coverage:	N/A

Note:

N/A

Directions for use:

Surface Preparation:

N/A

General Information:

N/A

THE CUSTOMER IS RESPONSIBLE FOR FOLLOWING THE RECOMMENDED APPLICATION PROCEDURES. FAILURE TO ADHERE TO THE RECOMMENDATIONS GIVEN IN THIS DATA SHEET WILL LIKELY RESULT IN UNSATISFACTORY FILM APPEARANCE OR FILM FAILURE. THE COMPLETE COATING SYSTEM SHOULD BE CHECKED FOR REQUIRED PROPERTIES PRIOR TO THE START-UP OF PRODUCTION

Drying Times:

	Room Temperature (20°C / 68°F)	Forced Drying Schedule (50°C / 122°F)
Tack Free Time:	N/A	N/A
Dry to Sand:	N/A	N/A
Dry to Stack:	N/A	N/A

Note:

N/A

Dry times are greatly affected by film build, porosity of substrate, air movement as well as heat and humidity. Temperatures are based on actual board temperature. This may vary depending on length of time for boards to reach these temperatures. Minimum curing temperatures of 64°F/18°C must be maintained throughout the curing cycle to achieve the film integrity as stated in product features.

These products are designed for industrial use only. AkzoNobel views safety as a top priority. Please refer to Material Safety Data Sheet for information on the safe use of this product.

Values shown are calculated estimates and should not be construed as product specifications. We cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and users assume all responsibility and liability for loss or damage arising from the use of our products whether used alone or a combination with other products. Use of unapproved or reclaimed solvent blends may reduce film properties and is not recommended.

Akzo Nobel Coatings, Inc
1431 Progress Ave
High Point, NC 27260
336-841-5111